



GIO-FLEX UR-AD PU CAD-CUT Heat Transfer Film with Sticky Carrier

This is made with a thin and soft polyurethane film for light weight and soft touch. Sticky PET carrier perfectly works for the details of artworks and easy on weeding.

Recommended Fabric: Cotton, Polyester, Cotton/Polyester Blends, Lycra.





APPLICATION INSTRUCTIONS

- 1. Cut in mirror image through adhesive layer (dull side) to the PET carrier.
- 2. Weed the excessive material and lay the cut-design on the fabric.
- 3. Heat Press at 150°C for 8 seconds and hot peel.



CARE INSTRUCTIONS FOR THE FINISHED PRODUCT









> Washing

Washer : Standard Household Washing Machine

Temperature : 60°C

Detergent : Standard Household Detergent Setting : Colored Clothing without Pre-wash

Maximum washing time on highest temperature not to exceed 12 minutes. Maximum total washing time not to exceed 50 minutes.

Test fabric for dye migration.

> Bleaching

Not Recommended

> Drying

Tumble Dry Low

> Ironing

Do not use steam, use a cool or warm temperature setting, avoid direct contact of the design, use a press cloth.





COLOR AVAILABILITY

Normal Color



Neon Color







SPECIFICATION

Standard Width	Roll Length	Q'ty / Carton	Weight / Carton	Volume / Carton
510 mm	25 MTS X 2	50 MTS	8.1 KGS	0.014 CBM
510 mm	50 MTS	50 MTS	7.7 KGS	0.013 CBM
1,020 mm	25 MTS	25 MTS	8.1 KGS	0.029 CBM

^{**} Thickness : 60~70 micron

STORAGE

- > Keep away from the direct sunlight, hot and humid place.
- > Use the within 2 years from the date of the lot number (production date).